

Soft PVC hose with rigid PVC spiral, suitable for use in particularly cold climates, for suction and delivery of liquids.



SMOOTH SURFACE \*\*\*\*\*

FLEXIBILITY SHORE A 48 \*\*\*\*\*

ABRASION RESISTANCE \*\*\*

TEMPERATURE RANGE  
-40 °c 45 °c

CHEMICAL RESISTANCE  
PVC OIL Table

CRUSHING RESISTANCE \*\*\*\*\*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	vacuum 23° m/H <sub>2</sub> O	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
51	2	50.8	61.8	3	9	9	165	5.5	4.8	9	right	1100	30	In stock
63	2 1/2	63.5	75.5	3	9	9	205	6	5.3	11	right	1450	30	In stock
76	3	76.2	89.2	3	9	9	260	6.5	6	11.5	right	1800	30	In stock
80		80	94	3	9	9	280	7	6.5	10.5	right	1900	30	In stock
89	3 1/2	89	103	2.5	9	7.5	300	7	6.5	11.8	right	2250	30	In stock
102	4	101.6	117	2	9	6	330	7.7	6.7	13	right	2800	30	In stock
110		110	126.4	1.5	9	4.5	360	8.2	7.2	11.5	right	3400	20	In stock
127	5	127	144	1	9	3	420	8.5	7.8	14	right	4000	20	In stock
152	6	152.4	170	1	9	3	510	8.8	8.5	15	right	5000	20	In stock