


Soft PVC hose with embedded galvanized steel spiral for suction and delivery of food liquids. Heavy duty version.



 SMOOTH SURFACE *****

 FLEXIBILITY ****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE
-5 °C 65 °C

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE ***

 FOR FOOD
Suitable for contact with foodstuff according to the declaration of conformity.

| Ø nominal mm | Ø nominal inch | Ø i.d. mm | Ø o.d. mm | vacuum 23° m/H ₂ O | working press. at 23° r.1:3 bar | bursting press. at 23° bar | bending radius mm | total thickness mm | Ø steel wire mm | spiral pitch mm | spiral direction | weight meter g/m | segment length m | coil length m | Availability |
|-----------------|-------------------|--------------|--------------|----------------------------------|---------------------------------------|-------------------------------|----------------------|-----------------------|--------------------|--------------------|------------------|---------------------|---------------------|------------------|--------------|
| 10 | 3/8 | 10 | 16 | 9.5 | 8 | 24 | 20 | 3 | 0.8 | 6.5 | right | 155 | | 60 | In stock |
| 12 | | 12 | 18 | 9.5 | 8 | 24 | 25 | 3 | 0.8 | 7 | right | 180 | | 60 | In stock |
| 14 | | 14 | 20 | 9.5 | 8 | 24 | 30 | 3 | 0.8 | 7.5 | right | 200 | | 60 | In stock |
| 16 | 5/8 | 16 | 22 | 9.5 | 8 | 24 | 35 | 3 | 0.8 | 7.5 | right | 225 | | 60 | In stock |
| 18 | | 18 | 24.5 | 9.5 | 7 | 21 | 40 | 3.3 | 1 | 8 | right | 280 | | 60 | In stock |
| 20 | | 20 | 27 | 9.5 | 6 | 18 | 50 | 3.5 | 1 | 8 | right | 340 | | 60 | In stock |
| 22 | 7/8 | 22 | 29 | 9.5 | 6 | 18 | 55 | 3.5 | 1 | 8.5 | right | 360 | | 60 | In stock |
| 25 | 1 | 25 | 33.5 | 9.5 | 6 | 18 | 60 | 4.3 | 1.4 | 13.5 | right | 510 | | 60 | In stock |
| 30 | | 30 | 40 | 9.5 | 5 | 15 | 70 | 5 | 1.4 | 14.5 | right | 680 | | 60 | In stock |
| 32 | 1 1/4 | 32 | 42 | 9.5 | 5 | 15 | 75 | 5 | 1.4 | 14.5 | right | 730 | | 60 | In stock |
| 35 | | 35 | 44.5 | 9.5 | 5 | 15 | 80 | 4.8 | 1.4 | 14.5 | right | 730 | | 60 | In stock |
| 38 | 1 1/2 | 38 | 49 | 9.5 | 5 | 15 | 90 | 5.5 | 1.6 | 15 | right | 950 | | 30 | In stock |
| 40 | | 40 | 53 | 9.5 | 5 | 15 | 100 | 6.5 | 2 | 17 | right | 1220 | | 30 | In stock |
| 45 | 1 3/4 | 45 | 58.5 | 9.5 | 5 | 15 | 110 | 6.75 | 2 | 18 | right | 1400 | | 30 | In stock |
| 50 | 2 | 50 | 63.5 | 9 | 5 | 15 | 125 | 6.8 | 2 | 18 | right | 1600 | | 30 | In stock |
| 60 | | 60 | 74 | 9 | 5 | 15 | 140 | 7 | 2.5 | 20 | right | 2050 | | 30 | In stock |
| 63 | 2 1/2 | 63 | 78 | 9 | 4 | 12 | 150 | 7.5 | 2.5 | 20 | right | 2250 | | 30 | In stock |
| 70 | | 70 | 86 | 9 | 4 | 12 | 180 | 8 | 2.5 | 20 | right | 2600 | | 30 | In stock |
| 75 | | 75 | 91 | 9 | 4 | 12 | 200 | 8 | 2.5 | 17 | right | 2850 | | 30 | In stock |
| 80 | | 80 | 96 | 9 | 3 | 9 | 220 | 8 | 2.5 | 17.5 | right | 3150 | | 30 | In stock |
| 90 | 3 1/2 | 90 | 107 | 9 | 3 | 9 | 260 | 8.5 | 3 | 18 | right | 3750 | | 30 | In stock |
| 100 | | 100 | 118 | 9 | 3 | 9 | 300 | 9 | 3 | 18.5 | right | 4400 | | 30 | In stock |
| 105 | | 105 | 122 | 9 | 2 | 6 | 310 | 8.5 | 2.5 | 19.5 | right | 3900 | | 20 | On demand |
| 110 | | 110 | 128 | 9 | 3 | 9 | 320 | 9 | 3 | 19 | right | 4650 | | 20 | In stock |
| 120 | | 120 | 138 | 9 | 2 | 6 | 340 | 9 | 3 | 19.5 | right | 5200 | | 20 | In stock |
| 125 | | 125 | 144 | 9 | 2 | 6 | 350 | 9.5 | 3 | 19.5 | right | 5400 | | 20 | In stock |
| 150 | | 150 | 170 | 9 | 2 | 6 | 450 | 9.5 | 3 | 18 | right | 7200 | | 20 | In stock |
| 203 | 8 | 203.8 | 223 | 9 | 2 | 6 | 900 | 9.6 | 3 | 19 | right | 9100 | 10 | | On demand |