



Hose with textile support in polyester covered with POLYURETHANE (PU) with crush-resistant spiral in PA 6, for suction of car exhaust fumes both on the floor and on overhead reels.




- 
SMOOTH SURFACE
\*\*\*


---

- 
FLEXIBILITY
\*\*\*


---

- 
ABRASION RESISTANCE
\*\*


---

- 
TEMPERATURE RANGE
-40 °c 200 °c


---

- 
CHEMICAL RESISTANCE
PU Table


---

- 
CRUSHING RESISTANCE
\*\*\*\*\*

---

- 
SELF-EXTINGUISHING
plastic material according to ul 94 v0 secondo classe m1

---

- 
CAUTION

do not coil the hose after use until it has cooled.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H <sub>2</sub> O	bending radius mm	wall thickness mm	rod diameter mm	spiral pitch mm	spiral direction	weight meter g/m	tensile breaking load kg	coil length m	Availability
50	2	52	62	5	80	0.35	3.5x6	20	left	330	>130	30	On demand
60		64	74	3.5	90	0.35	3.5x6	20	left	400	>130	30	On demand
75		77	87	1.5	100	0.35	3.5x6	20	left	480	>130	30	On demand
100		103	114	1	150	0.35	4x6.5	20	left	700	>130	30	On demand
125		128	139	0.8	200	0.35	4x6.5	20	left	850	>130	30	On demand
150		153	164	0.6	230	0.35	5x7.5	25	left	1200	>130	30	On demand
200		205	216	0.5	300	0.35	5x7.5	25	left	1600	>130	20	On demand