


PVC hose with rigid PVC spiral for jacuzzis, swimming pool supply and recirculation as a substitute for common rigid hoses.



 SMOOTH SURFACE *****

 FLEXIBILITY ***

 ABRASION RESISTANCE *****

 TEMPERATURE RANGE
-5 °C 60 °C

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE *****

 CALIBRATED DIAMETERS *****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	vacuum 23° m/H ₂ O	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
14		14	20.2	7	7	21	60	3.1	2,3x4	6	right	210	30	In stock
15		15	20.2	7	7	21	60	2.6	2,4x3,7	5.5	right	180	30	In stock
16	5/8	16	21.8	7	7	21	65	2.9	2,2x4	6.2	right	210	30	In stock
20		20	25.4	7	7	21	80	2.7	2,5x4	6.7	right	250	30	On demand
20		20	25.5	7	7	21	80	2.8	2,5x4	6.7	right	250	30	On demand
20.5		20.4	26.6	7	7	21	82	3.1	2,5x4	6.5	right	290	30	On demand
25	1	25	32.1	7	7	21	100	3.5	3,2x4,5	7	right	395	30	In stock
25	1	25	33	7	7	21	100	4	2,8x4,8	7	right	480	30	In stock
25	1	25	33.9	7	7	21	100	4.5	2,8x4,8	7	right	500	30	In stock
27		27	33.6	7	7	21	110	3.3	2,5x4,5	5.8	right	400	30	On demand
27		27	33.8	7	7	21	110	3.4	2,3x4	5.8	right	400	30	In stock
32	1 1/4	31.6	40	7	7	21	128	4.2	3,2x4,7	8	right	600	30	In stock
40		40	48.1	6	7	18	160	4.1	3x5	8.7	right	720	30	On demand
40		40	48.5	6	7	18	160	4.2	3x5	8.7	right	730	30	In stock
40		40	50.1	6	7	18	160	5.1	4.7	8.7	right	930	30	In stock
40		40	50.3	6	7	18	160	5.1	4.5	8.7	right	930	30	In stock
42		42	50	6	7	18	160	4.1	3.8	7	right	785	30	In stock
43		43	50.3	5	7	15	175	3.6	3x5	8.7	right	680	30	In stock
50	2	50.8	60.2	5	7	15	200	4.7	3,5x5	9.8	right	1060	30	In stock
50.8	2	51	63.2	5	7	15	210	6.1	4,3x5	10.5	right	1380	30	On demand
55		55	63.3	5	7	15	220	4.1	3.9	7.5	right	1000	30	In stock
65		65	75.2	5	7	15	260	5.1	4.5	8.1	right	1400	30	In stock