

Flexible layflat PVC hose, with polyester yarn reinforcement resistant to elongation, for pressurized delivery of liquids in general.



 SMOOTH SURFACE \*\*\*\*\*

 FLEXIBILITY \*

 ABRASION RESISTANCE \*\*\*\*

 TEMPERATURE RANGE  
-5 °c 60 °c

 CHEMICAL RESISTANCE  
PVC Table

 CRUSHING RESISTANCE \*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	total thickness mm	weight meter g/m	# wires for angle n° x a°	working resistance kg	tensile breaking load kg	coil length m	Availability
38	1 1/2	38	40	2.5	1.5	1	7.5	1	175	32x75°	144	335	100	In stock
40		41	43	2.5	1.5	1	7.5	1	190	32x70°	150	350	100	In stock
45	1 3/4	45	47	2.5	1.5	1	7.5	1	210	36x70°	165	384	100	On demand
51	2	51	53	2.5	1.5	1	7.5	1	270	36x70°	190	445	100	In stock
60		60	63	2	1	0.5	6	1.5	300	48x70°	212	495	100	In stock
63	2 1/2	63.5	66	2	1	0.5	6	1.5	340	48x70°	228	530	100	In stock
76	3	76	79	2	1	0.5	6	1.5	380	60x70°	268	625	100	In stock
80		80	83	1.5	0.8	0.3	4.5	1.5	390	60x70°	280	655	100	In stock
102	4	102	105	1.5	0.8	0.3	4.5	1.5	500	72x70°	356	830	100	In stock
152	6	152	156	1	0.5	0.2	3	2	1050	72x80°	530	1250	100	On demand