

PVC hose with rigid PVC spiral, for delivery and suction of food liquids.



 SMOOTH SURFACE \*\*\*\*\*


 FLEXIBILITY \*\*\*\*

 ABRASION RESISTANCE \*\*\*\*\*

 TEMPERATURE RANGE  
-5 °c 60 °c

 CHEMICAL RESISTANCE  
PVC Table

 CRUSHING RESISTANCE \*\*\*\*

 FOR FOOD  
Suitable for contact with foodstuff according to the declaration of conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	vacuum 23° m/H <sub>2</sub> O	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
18		18	24	8	7	24	65	3	2,3x3,5	6.6	right	260	50	On demand
19	3/4	19	24.6	8	7	24	70	2.8	2,5x3,5	7	right	250	50	On demand
20		20	26.2	8	7	24	75	3.1	2,5x4	6.8	right	275	50	In stock
25	1	25	31.6	8	7	24	120	3.3	3,2x3,4	7.4	right	330	50	In stock
30		30	37	7	7	21	140	3.5	3,4x3,6	7.5	right	420	50	In stock
32	1 1/4	32	39.2	7	7	21	150	3.6	3,4x3,6	7.7	right	460	50	In stock
35		35	41.8	7	7	21	160	3.4	3,4x3,6	7.7	right	500	50	In stock
38	1 1/2	38	45.4	6.5	7	19.5	170	3.7	3.6	7.6	right	550	50	In stock
40		40.3	47.6	6.5	7	19.5	180	3.8	3.6	7.8	right	610	50	In stock
45	1 3/4	45	52.4	6.5	7	19.5	200	3.7	3.5	8	right	670	50	In stock
50	2	50	58.4	6	7	18	220	4.2	4	8.3	right	810	50	In stock
51	2	51.3	59.5	6	7	18	225	4.1	4	8.5	right	810	50	On demand
55		55	63.8	6	7	18	250	4.4	4.1	9.8	right	860	50	On demand
60		60	69	5	7	15	270	4.5	4.4	8.3	right	970	50	In stock
63	2 1/2	63	71.2	5	7	15	290	4.1	3.9	8.5	right	1040	50	In stock
65		65	74					4.5	4.2	8.1	right	1050	50	On demand
70		70	79.2	4	7	12	320	4.6	4.2	8.8	right	1200	50	In stock
75		75	85.2	4	7	12	350	5.1	4.8	9.5	right	1380	50	In stock
76		76	86	4	7	12	350	5	4.6x5	12	right	1380	50	On demand
80		80.2	90.8	4	7	12	360	5.3	5	10.5	right	1560	25	In stock
90	3 1/2	90	100.4	4	7	12	430	5.2	5	10.9	right	1800	25	In stock
100		100	112	4	7	12	480	6	5.5	11.3	right	2160	25	In stock
102	4	102.3	114.9	4	7	12	480	6.3	5.8	11.3	right	2160	25	In stock
110		110	122	4	6	12	530	6	5.6	11.5	right	2400	25	In stock
120		121	133.4	3	6	9	680	6.2	6	11.5	right	2800	25	In stock
125		125	137.4	3	6	9	730	6.2	6	11.5	right	3130	25	In stock
127	5	127	140.6	3	6	9	730	6.8	6.1	12.3	right	3130	25	On demand
150		150	164.4	3	5	9	810	7.2	6.6	14	right	4250	25	In stock
152	6	152.4	167.2	3	5	9	810	7.4	6.8	14.5	right	4250	25	On demand
200		200	218	2	5	6	900	9	8.5	21.5	right	6400	10	In stock