

PVC-PHF hose with rigid PVC spiral, for heavyduty use in the wine and dairy sector, for suction and delivery of food liquids, alcoholic food liquids up to 50% and milk products.



 SMOOTH SURFACE *****


 FLEXIBILITY ***

 ABRASION RESISTANCE *****

 TEMPERATURE RANGE
-5 °C 60 °C

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE *****

 FOR FOOD
Suitable for contact with foodstuff according to the declaration of conformity.

 O-PHTHALATE FREE *****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	vacuum 23° m/H ₂ O	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø rigid spiral (AxB if oval) mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	32.6	8	9	24	175	3.8	3.5	7	right	400	50	In stock
30		30	37.5	8	9	24	210	3.8	3.5	7.5	right	500	50	In stock
32	1 1/4	32	39.6	8	9	24	220	3.8	3.5	7.5	right	520	50	In stock
35		35	42.5	8	9	24	240	3.8	3.6	7.5	right	600	50	In stock
38	1 1/2	38	46.4	8	9	24	250	4.2	3.8	7.5	right	700	50	In stock
40		40	49	8	9	24	260	4.5	4.1	7.8	right	750	50	In stock
45	1 3/4	45	54	8	9	24	290	4.5	4.1	8.5	right	900	50	In stock
50	2	50	59	8	9	24	325	4.5	4.3	8.5	right	1000	50	In stock
60		60	71	7	9	21	380	5.5	5.3	10	right	1450	50	In stock
63	2 1/2	63	75	7	9	21	400	6	5.5	8.5	right	1670	50	In stock
70		70	82	6	9	18	450	6	5.3	10.5	right	1800	50	In stock
75		75.5	87.5	6	9	18	490	6	5.3	12	right	1900	50	In stock
80		80	93	5	9	15	530	6.5	6	12.5	right	2200	50	In stock
90	3 1/2	90	104	5	9	15	600	7	6.5	13.5	right	2480	30	On demand
100		100	116	4	9	12	700	8	7.2	13.5	right	3300	30	In stock
102	4	102	117	4	9	12	700	7.5	7	13.5	right	3300	30	On demand
110		110	125.6	4	9	12	800	7.8	7.5	14.5	right	3450	30	In stock
120		120	136	4	9	12	900	8	8	17	right	3600	30	In stock
125		125	140.6	4	9	12	980	7.8	7.2	12	right	4200	30	In stock
150		150	170	3	9	9	1350	10	8.5	13.5	right	6300	30	In stock
200		200	224	2	9	6	1800	12		22	right	8500	10	On demand