

Soft PVC hose with POLYURETHANE (PU) underlayer with polyester yarn reinforcement and PU adhesive middle layer, for pressurized transfer of oil, diesel oil, blue diesel, urea (ISO 22241).



- 
SMOOTH SURFACE
\*\*\*\*\*

---

- 
FLEXIBILITY
\*\*\*

---

- 
ABRASION RESISTANCE
\*\*\*

---

- 
TEMPERATURE RANGE
-10 °c 60 °c

---

- 
CHEMICAL RESISTANCE
PU Table

---

- 
CRUSHING RESISTANCE
\*\*\*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
12.7	1/2	12,7	18.5	15	10	6	45	80	205	18x54°		On demand
13		13	21	15	10	6	45	100	270	18x54°		On demand
19	3/4	19	26	15	10	6	45	130	350	24x54°	50	On demand
19.5	3/4	19.2	26.5	15	10	6	45	130	360	24x54°		On demand
25	1	25	35	15	10	6	45	180	640	36x54°	50	On demand