

PVC hose with square section rigid PVC spiral, HAYCLOR substrate, for suction and delivery of liquids for supply and pool recirculation.



Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	vacuum 23° m/H ₂ O	bursting press. at 23° bar	bending radius mm	total thickness mm	liner thickness mm	Rigid wire size mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
25	1	25	32.1	8	7	24	100	3.6	0.3	4.3x3	7	right	400	30/50	On demand
42		42	50.3	7	7	21	160	4.1	0.3	4.8x3.6	6.5	right	750	30/50	In stock
43		43	50.3	7	7	21	170	3.7	0.3	4.6x3.3	6.8	right	680	30/50	In stock
50	2	50	59	6	7	18	200	4.5	0.3	3.5x5	7	right	1000	30/50	On demand
55		55	63.3	5	7	15	220	4.2	0.3	5.2x3.6	7.5	right	1000	30/50	In stock

 SMOOTH SURFACE *****

 FLEXIBILITY ****

 ABRASION RESISTENCE *****

 TEMPERATURE RANGE
-5 °c 60 °c

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE *****

 CHLORINE RESISTANCE *****

 MOULD RESISTANCE