

Soft PVC hose with polyester yarn reinforcement and intermediate bonding PU adhesive layer for passage of air under pressure. (*) Double meshing.



 SMOOTH SURFACE *****

 FLEXIBILITY *****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE
-5 °c 60 °c

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE ***

 OZONE RESISTANCE *****

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
5	3/16	5	10.5	20	18	16	60	20	2.75	92	12x50°	100	On demand
6	1/4	6	14	20	18	16	60	25	4	175	18x50°	100	In stock
7		7	16	20	18	16	60	20	4.5	220	18x54°	100	In stock
8	5/16	8	12	20	18	16	60	22	2	90	18x54°	100	On demand
8	5/16	8	14	20	18	16	60	25	3	120	18x54°	100	On demand
8	5/16	8	15	20	18	16	60	28	3.5	175	18x54°	100	On demand
8	5/16	8	17	20	18	16	60	30	4.5	245	24x50°	100	In stock
10	3/8	10	15	20	18	16	60	28	2.5	120	24x54°	100	On demand
10	3/8	10	16	20	18	16	60	30	3	160	24x54°	100	On demand
10	3/8	10	19	20	18	16	60	32	4.5	270	24x54°	100	In stock
13	1/2	13	19	20	18	16	60	40	3	190	24x54°	100	On demand
13	1/2	13	23	20	18	16	60	40	5	380	24x54°	100	In stock
16	5/8	16	26	20	18	16	60	50	5	440	24x54°	50	In stock
19	3/4	19	26	20	18	16	60	55	3.5	350	24+24 (*)	60	On demand
19	3/4	19	30	20	18	16	60	60	5.5	560	24+24 (*)	60	In stock
25	1	25	37	20	18	16	60	85	6	765	36+36 (*)	60	In stock