

Soft PVC hose with polyester yarn reinforcement for water transport in agriculture and flower growing.



 SMOOTH SURFACE *****

 FLEXIBILITY *****

 ABRASION RESISTANCE ***

 TEMPERATURE RANGE
-5 °c 60 °c

 CHEMICAL RESISTANCE
PVC Table

 CRUSHING RESISTANCE ***

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	bursting press. at 23° bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
10	3/8	10	15	8	24	54	2.5	125	12x50°	50	In stock
12		12	16.5	6	18	90	2.3	115	18x50°	50	In stock
13	1/2	13	18	8	24	64	2.5	155	18x50°	50	In stock
13	1/2	13	19	8	24	78	3	180	18x50°	50	In stock
15		15	18.5	6	18	52	1.8	135	18x45°	50	In stock
16	5/8	16	21	8	24	96	2.5	190	24x45°	50	In stock
16	5/8	16	22	8	24	90	3	230	24x40°	50	In stock
18		18	23.4	6	18	95	2.7	230	24x40°	50	In stock
19	3/4	19	25	7	21	100	3	275	24x45°	50	In stock
19	3/4	19	26	7	21	105	3.5	310	24x45°	50	In stock
22		22	29	7	21		3.5	370	24x45°	50	In stock
25	1	25	32	6	18		3.5	400	24x54°	50	In stock
25	1	25	33	6	18	310	4	460	24x54°	50	In stock
30		30	38	6	18		4	560	24x54°	50	In stock
35		35	43	5	15		4	700	24x60°	50	In stock
40		40	49	4	12	525	4.5	840	24x65°	50	In stock
50	2	50	60	4	12		5	1300	48x50°	25	In stock