

Soft PVC hose with polyester yarn reinforcement, for transporting industrial liquids, chemical solutions and compressed air.



 SMOOTH SURFACE \*\*\*\*\*

 FLEXIBILITY \*\*\*\*\*

 ABRASION RESISTANCE \*\*\*\*

 TEMPERATURE RANGE  
-10 °c 60 °c

 CHEMICAL RESISTANCE  
PVC Table

 CRUSHING RESISTANCE \*\*\*\*

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	Crush Resistance N	coil length m	Availability
6	1/4	6	11	20	16	12	60	17	80	12x50°	450	100	On demand
6	1/4	6	12	20	16	12	60	15	105	12x50°		100	On demand
8	5/16	8	13	18	13	9	54	23	105	16x50°	345	100	On demand
8	5/16	8	14	18	13	9	54	21	125	16x50°		100	On demand
10	3/8	10	15	18	13	9	54	45	120	18x50°	250	100	On demand
10	3/8	10	16	18	13	9	54	36	150	18x50°	326	100	On demand
12		12	17	12	9	5	36	55	130	18x52°	125	50	On demand
13	1/2	13	18	12	9	5	36	45	150	18x52°		50	On demand
16	5/8	16	21	10	7	4	30	65	185	24x50°		50	On demand
19	3/4	19	25	10	7	4	30	100	260	24x50°		50	On demand
25	1	25	32	8	5	3	24	150	390	24x54°		50	On demand
35		35	45	7	4	2	21	300	750	36x54°		50	On demand
40		40	50	7	4	2	21	350	880	48x54°		50	On demand