

Antiabrasive POLYURETHANE (PU) and thermoplastic rubber compound hose with polyester yarn reinforcement supplied with machines required by the ATEX directive, for pneumatic tools in general, airbrushes, and paint sprayers.



Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	working press. at 40° bar	working press. at 60° bar	bursting press. at 23° bar	bending radius mm	total thickness mm	weight meter g/m	# wires for angle n° x a°	Crush Resistance N	coil length m	Availability
6	1/4	6	10	20	17	15	60	20	2	65	24x54°	230	100	On demand
8	5/16	8	12	20	17	15	60	22	2	85	18x52°	220	60	On demand
10	3/8	10	15	20	17	15	60	38	2.5	130	24x52°	170	50	On demand
10	3/8	10	19	20	17	15	60	25	4.5	240	24x55°	200		On demand
13	1/2	13	19	20	17	15	60	65	3	195	24x54°	140	30	On demand
16	5/8	16	23	20	17	15	60	60	3.5	250	24x54°	200	25	On demand

SMOOTH SURFACE *****

FLEXIBILITY *****

ABRASION RESISTANCE ***

TEMPERATURE RANGE
-15 °c 60 °c

CHEMICAL RESISTANCE
PU Table

CRUSHING RESISTANCE ***