

Antiabrasive POLYURETHANE (PU) hose with polyester yarn reinforcement for the delivery of compressed air.



 SMOOTH SURFACE *****

 FLEXIBILITY SHORE A 57 **


 ABRASION RESISTANCE *****

 TEMPERATURE RANGE
-35 °c 80 °c

 CHEMICAL RESISTANCE
PU Table

 CRUSHING RESISTANCE *****

 OZONE RESISTANCE *****

 FOR FOOD
Suitable for contact with foodstuff according to the declaration of conformity.

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	working pressure at 23° bar	bursting press. at 23° bar	bending radius mm	weight meter g/m	# wires for angle n° x a°	coil length m	Availability
6	1/4	6	10	20	60	20	60	24x45°	100	In stock
7.5		7.5	11.5	20	60		75	24x55°		On demand
8	5/16	8	12	20	60	30	75	24x55°	50	In stock
8.5		8.5	12.5	20	60		90	24x55°		On demand
10	3/8	10	14.5	20	60		115	24x51°		On demand
10	3/8	10	15	20	60	35	120	24x51°	50	In stock
13	1/2	13	19	20	60	55	200	20x54°		On demand