

Hose made of polyester textile covered with PVC with galvanized steel spiral embedded between two layers of textile, for air-conditioning, suction of fumes and hot air.



SMOOTH SURFACE ******

FLEXIBILITY *********

ABRASION RESISTANCE ******

TEMPERATURE RANGE
-5 °c 80 °c

CHEMICAL RESISTANCE
for short periods up to -20°C +110°C
PVC Table

CRUSHING RESISTANCE *******

SELF-EXTINGUISHING
italian ministerial decree 26.06.1984 with test methods uni 8457 - 8757/a1 - 9174 - 9174/a1.

| Ø nominal mm | Ø nominal inch | Ø i.d. mm | Ø o.d. mm | working pressure at 23° bar | vacuum 23° m/H ₂ O | bending radius mm | total thickness mm | wall thickness mm | Ø steel wire mm | spiral pitch mm | spiral direction | weight meter g/m | coil length m | Availability |
|-----------------|-------------------|--------------|--------------|--------------------------------|----------------------------------|----------------------|-----------------------|----------------------|--------------------|--------------------|------------------|---------------------|------------------|--------------|
| 40 | | 41 | 44 | 0.55 | 1 | 20 | | 0.22 | 0.8 | 20 | left | 85 | 12 | In stock |
| 51 | 2 | 51 | 54 | 0.5 | 0.95 | 25 | | 0.22 | 0.8 | 20 | left | 105 | 12 | In stock |
| 63 | 2 1/2 | 63 | 66 | 0.45 | 0.9 | 31 | | 0.22 | 0.8 | 20 | left | 130 | 12 | In stock |
| 70 | | 70 | 73 | 0.43 | 0.85 | 35 | | 0.22 | 0.8 | 20 | left | 145 | 12 | In stock |
| 76 | 3 | 76 | 79 | 0.4 | 0.8 | 36 | | 0.22 | 0.8 | 20 | left | 155 | 12 | In stock |
| 82 | | 82 | 85 | 0.38 | 0.75 | 41 | | 0.22 | 0.8 | 20 | left | 170 | 12 | In stock |
| 89 | 3 1/2 | 89 | 92 | 0.3 | 0.7 | 44 | | 0.22 | 0.8 | 20 | left | 180 | 12 | In stock |
| 102 | 4 | 102 | 105 | 0.25 | 0.65 | 51 | | 0.22 | 1 | 25 | left | 215 | 12 | In stock |
| 108 | | 108 | 111 | 0.23 | 0.6 | 54 | | 0.22 | 1 | 25 | left | 230 | 12 | On demand |
| 114 | | 114 | 117 | 0.21 | 0.55 | 57 | | 0.22 | 1 | 25 | left | 240 | 12 | In stock |
| 121 | | 121 | 124 | 0.20 | 0.5 | 60 | | 0.22 | 1 | 25 | left | 255 | 12 | In stock |
| 127 | 5 | 127 | 130 | 0.18 | 0.45 | 63 | | 0.22 | 1 | 25 | left | 265 | 12 | In stock |
| 133 | | 133 | 136 | 0.16 | 0.4 | 66 | | 0.22 | 1 | 25 | left | 280 | 12 | In stock |
| 140 | | 140 | 143 | 0.15 | 0.38 | 70 | | 0.22 | 1 | 25 | left | 295 | 12 | In stock |
| 152 | 6 | 152 | 156 | 0.14 | 0.35 | 76 | | 0.22 | 1.4 | 32 | left | 380 | 12 | In stock |
| 160 | | 161 | 165 | 0.12 | 0.32 | 80 | | 0.22 | 1.4 | 32 | left | 410 | 12 | On demand |
| 165 | | 165 | 169 | 0.12 | 0.3 | 82 | | 0.22 | 1.4 | 32 | left | 420 | 12 | In stock |
| 178 | | 178 | 182 | 0.1 | 0.25 | 89 | | 0.22 | 1.4 | 32 | left | 450 | 12 | In stock |
| 203 | 8 | 203 | 207 | 0.08 | 0.2 | 101 | | 0.22 | 1.4 | 32 | left | 510 | 12 | In stock |
| 228 | 9 | 228 | 232 | 0.06 | 0.15 | 114 | | 0.22 | 1.4 | 32 | left | 570 | 12 | In stock |
| 254 | 10 | 254 | 258 | 0.05 | 0.12 | 127 | | 0.22 | 1.6 | 40 | left | 640 | 12 | In stock |
| 279 | | 279 | 283 | 0.04 | 0.1 | 139 | | 0.22 | 1.6 | 40 | left | 700 | 12 | In stock |
| 304 | 12 | 304 | 308 | 0.03 | 0.05 | 152 | | 0.22 | 1.6 | 40 | left | 770 | 12 | In stock |
| 330 | | 330 | 334 | 0.02 | 0.03 | 165 | | 0.22 | 1.6 | 40 | left | 830 | 12 | In stock |
| 355 | 14 | 355 | 359 | 0.02 | 0.02 | 177 | | 0.22 | 1.6 | 40 | left | 890 | 12 | In stock |
| 406 | 16 | 406 | 410 | 0.02 | 0.01 | 203 | | 0.22 | 1.6 | 40 | left | 1030 | 12 | In stock |
| 457 | 18 | 457 | 462 | 0.01 | 0.0005 | 228 | | 0.22 | 1.8 | 40 | left | 1300 | 12 | In stock |
| 508 | 20 | 508 | 513 | 0.01 | 0.0004 | 254 | | 0.22 | 1.8 | 40 | left | 1450 | 12 | In stock |
| 558 | 22 | 558 | 563 | 0.01 | 0.0003 | 279 | | 0.22 | 1.8 | 40 | left | 1580 | 12 | In stock |
| 610 | 25 | 610 | 615 | 0.01 | 0.0002 | 305 | | 0.22 | 1.8 | 40 | left | 1730 | 12 | In stock |