

Two-layer soft PVC hose with embedded galvanised steel spiral with polyester yarn reinforcement, for suction and delivery of liquids.



Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H ₂ O	working press. at 23° r.1:3 bar	working press. at 23° r.1:4 bar	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	Segment Length m	coil length m	Availability
19	3/4	19	28	9	20	16	60	70	4.5	1	8.5	right	475		60	On demand
25	1	25	36	9	16	12	48	80	5.5	1.2	9	right	680		60	In stock
30		30	40.5	9	16	12	48	90	5.3	1.2	9.5	right	770		60	In stock
32	1 1/4	32	42.5	9	16	12	48	100	5.3	1.2	9.5	right	800		60	In stock
35		35	47	9	14	10	42	115	6	1.4	10	right	1100		60	On demand
38	1 1/2	38	51	9	14	10	42	125	6.5	1.4	10.5	right	1200		30	In stock
40		40	52	9	14	10	42	130	6	1.4	11	right	1200		30	In stock
45	1 3/4	45	58	9	12	10	36	140	6.5	1.4	11	right	1400		30	On demand
50	2	50	63.5	9	12	10	36	150	6.8	1.6	11	right	1600		30	In stock
60		60	74	9	12	10	36	180	7	1.6	11	right	2000		30	In stock
63	2 1/2	63	77	9	12	10	36	190	7	1.6	11	right	2100		30	In stock
75		75	91	9	12	10	36	190	8	2	13.5	right	2950		30	In stock
76	3	76	92	9	12	9	36	210	8	2	13.5	right	2970		30	In stock
80		80	96	9	10	8	30	220	8	2	14	right	3020		30	In stock
90	3 1/2	90	106.5	9	10	8	30	250	8.3	2	14	right	3500		30	In stock
100		100	117	9	10	8	30	300	8.5	2	14.5	right	4050		30	In stock
102	4	102	119	9	10	8	30	300	8.5	2	14.5	right	4150		30	In stock
120		120	138	9	8	6	24	350	9	2.5	15	right	5430		20	In stock
127	5	127	145	9	7	5	22	370	9	2.5	15	right	5950		20	In stock
150		150	169	9	5	3	15	480	9.5	2.5	15.5	right	7000		20	In stock
152	6	152	171	9	5	3	15	480	9.5	2.5	15.5	right	7050		20	In stock
200		200.5	222	9	3	2.5	9	650	10.7	3	22	right	10300	12		In stock
203 (**)	8	203.2	225	9	3	2.5	9	650	10.9	3	17.5	right	11000	12		On demand

* CODE 912805 VACUPRESS FLEX PLUS