

Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement with copper braid for an anti-static rendering, with outer cover made of antiabrasive PU, for suction and delivery of oils, blue diesel, diesel and bio diesel.



 SMOOTH SURFACE *****

 FLEXIBILITY ***

 TEMPERATURE RANGE
-25 °c 60 °c

 CHEMICAL RESISTANCE
PVC OIL Table

 CRUSHING RESISTANCE ***

 ANTISTATIC
<2 ohm/m

Ø nominal mm	Ø nominal inch	Ø i.d. mm	Ø o.d. mm	vacuum 23° m/H ₂ O	working press. at 23° r.1:3 bar	working press. at 23° r.1:4 bar	bursting press. at 23° bar	bending radius mm	total thickness mm	Ø steel wire mm	spiral pitch mm	spiral direction	weight meter g/m	coil length m	Availability
76	3	76	90.5	9	10	8	30	210	7.25	2	13.5	right	2700	30	In stock
80		80	94.5	9	10	8	30	220	7.3	2	14	right	2800	30	In stock
90	3 1/2	90	105.5	9	10	8	30	250	7.8	2	14	right	3250	30	On demand
102	4	102	117.5	9	10	8	30	300	7.8	2	14.5	right	3700	30	In stock
120		120	137	9	8	6	24	450	8.5	2.5	15	right	4750	20	In stock
127	5	127	144	9	7	5	21	480	8.5	2.5	15	right	5300	20	On demand
150		150	167.5	9	5	3	15	550	8.8	2.5	15.5	right	6300	20	In stock
152	6	152	169.5	9	5	3	15	550	8.8	2.5	15.5	right	6350	20	In stock